

Renewable Energy Division  
3M™ Automotive Window Film Metallic Shade



Look **Hot**  
Feel Cool

## 3M™ Automotive Window Film Metallic Shade

- Low cost dyed and metalised heat gain reduction technology
- Protect vehicle occupants from uncomfortable heat and glare
- Sun Protection Factor of 100
- Reduce reliance on air conditioning reducing fuel consumption



# 3M™ Automotive Window Film Metallic Shade

## Description

3M's Metallic Shade Series is a range of low cost dyed metalised polyester films. The hybrid technology behind these easy to maintain films provides maximum heat rejection. Additionally, the films block almost the entire amount of UVA and UVB rays which are the main cause of fading and skin damage. The Metallic Shade Series rejects up to 49% of the total solar energy coming through your windows, providing a "cool effect" in more ways than one. The films have a scratch resistant coating, and several different shading levels in an attractive charcoal hue.

- Entry level durability performance
- Customise vehicles with tinted glass aesthetics
- Solar energy rejection stabilises in-car temperature
- Optimal temperatures make vehicle occupants feel more comfortable
- Feel secure with privacy from the outside world

## Application

The Metallic Shade Series is intended for use on the inside surface of vehicle windows. 3M Automotive Window Film is to be professionally applied by skilled, well-trained, 3M authorised installers. Windows can be considered operational after 24 hours.

## Physical Properties

Thickness (MS 5)	0.071mm/ 71µm
Thickness (all others)	0.058mm/ 58µm
Colour	Black metallic to slightly tinted metallic
Film material	Polyester
Adhesive	Permanent, pressure sensitive acrylic
Top coating	Abrasive resistant hard coat

## Cleaning

3M Automotive Window Films may be cleaned 14 days after installation using ordinary automotive window cleaning agents and avoiding the use of abrasive particles. Do not use rough sponges, cloths or brushes. Synthetic sponges, soft wipes or rubber squeegee cleaners are recommended.

## Shelf Life

To ensure the longest shelf life possible, be sure to store the film according to the guidelines given in each box. Recommended storage conditions for all films are 21°C and 40 – 50 % relative humidity. Films should be kept in the original packaging and not exposed to heat, light or relative humidity above 50%. When stored according to these recommendations, a shelf life of at least 5 years can be expected.

Film Type on 6mm Glass	Visible Light Transmitted	Visible Light Reflected	Total Solar Energy Rejected	Heat Gain Reduction	UV Rejection	Glare Reduction
No film	89%	8%	19%	N/A	38%	N/A
MS 5	5%	5%	49%	37%	99%	95%
MS 25	25%	6%	44%	31%	99%	75%
MS 35	36%	6%	40%	26%	99%	64%
MS 55	58%	7%	34%	19%	99%	42%

The technical information, recommendations and other statements contained in this document are based upon European and/ or US tests or experience that 3M believes are reliable, but the accuracy or completeness of such information is not guaranteed. Many factors beyond 3M's control and uniquely within the user's knowledge and control can affect the use and performance of a 3M product in a particular application. Given the variety of factors that can affect the use and performance of a 3M product, the user is solely responsible for evaluating the 3M product and determining whether it is fit for a particular purpose, suitable for user's method of application and will fulfil the local law for automotive windows. The information provided in this report is believed to be reliable; however, due to the wide variety of intervening factors, 3M does not warrant that the results will necessarily be obtained. All issues regarding warranty and liability for the product and the effect of its use are governed in accordance with the provisions of the appropriate contract of sale unless local laws dictate otherwise.



**Renewable Energy Division**  
**3M United Kingdom plc**  
 3M Centre  
 Cain Road, Bracknell  
 Berkshire RG12 8HT  
 3M.eu/AutoTinting

Autorizētais logu plēvju uzstādītājs un izplatītājs:



Saules Stikli SIA  
 Maskavas iela 449, Rīga, LV-1063  
 tel. +371 6713 1662 | pleves@logi.lv  
 www.StikluTonesana.LV

16835  
 Please recycle.  
 © 3M 2013. All rights reserved.